

RedGard has a lot less of one thing. Cure Time.

- Dries 30% faster
- Easy to use
- Meets ANSI A118.10, A118.12
- IAPMO rated as a shower pan liner with no fabric



**FOR YOUR MOST CHALLENGING INSTALLATIONS AND DEADLINES.
WE KNOW SURFACE PREPARATION. COUNT ON CUSTOM.**



Get the free mobile app for your phone
<http://gettag.mobi>

custombuildingproducts.com

800-272-8786

SS113 1/15R



CUSTOM®

TILE INSTALLATION SYSTEMS

RedGard® Waterproofing and Anti-Fracture Membrane

WATERPROOFING

BENEFITS:

Creates a continuous waterproof barrier
Bonds directly to metal drains, PVC, stainless and ABS drain assemblies
No reinforcing fabric needed
Flood Test in 24 Hours

INSTALLATIONS:

Showers, tubs, steam showers and steam rooms
Swimming pools and fountains
Spas and hot tubs
Terraces and balconies
Facades

Approvals:

- Exceeds ANSI A118.10 requirements
- Meets Uniform Plumbing Code specifications for use as a shower pan liner

ANTI-FRACTURE

BENEFITS:

Isolates existing cracks to 1/8" (3 mm)
Rated Extra Heavy-Duty
Thin application adds no appreciable thickness to floor
Tile in 1-1 1/2 hours

INSTALLATIONS:

Suspended or on grade
Malls, airports and lobbies
Heavy industrial applications

Approvals:

- Exceeds ANSI A118.12 requirements

Areas of Use (Substrates):

- Concrete, cement mortar beds, masonry
- WonderBoard® Lite, cement backerboards
- Exterior grade plywood — For crack isolation of interior dry areas only
- Exterior decks — Contact Technical Services for information related to exterior applications and the use of pressure treated wood decks
- Lightweight concrete
- Gypsum-based cement toppings



ITEM CODE	SIZE
LQWAF1	1 gallon (3.78 L) Pail
LQWAF3	3.5 gallon (13.2 L) Pail

Coverage:

For waterproofing and anti-fracture membrane — two 25-30 mil coats. The combined dried coating needs to be a minimum of 25-30 mils thick or 50-60 mils when wet and should not exceed 90 mils wet.

