

EASY DOES IT

Not really an installation kind of person? Don't worry. Most of us aren't. That's why we make portable air conditioners. This one has 10,200 BTU (ASHRAE 128 STD) / 6,500 BTU, Auto Swing and even an LCD remote. Which means you can control the temperature even when you're not there. Cool, huh?

PERFORMANCE

- 10,000 BTU (ASHRAE 128 STD)
- 6,500 BTU
- Dehumidification (Pt/Hr) 2.5
- Est. Cooling Area 300 sq. ft. (Room size 15' x 20')

FEATURES

- Programmable 24-Hour On/Off Timer
- Multiple Fan Speeds with Auto Cool
- Auto Evaporation System
- LCD Remote Control
- Timer 24 Hr. On/Off
- Window Installation Kit



Programmable 24-Hour On/Off Timer

With our programmable 24-hour on/off timer, you can control the temperature even when you're not there.

Auto Swing Air Vent

Enjoy every bit of cool air with our oscillating air vent technology. It circulates your cool air more efficiently, so no hot spot will be left untouched.

Auto Evaporation System

Allows continuous use without having to empty a water bucket.

PERFORMANCE

BTU Performance (ASHRAE 128 STD)	10,000
BTU Performance	6,500
Dehumid. (Pt/Hr)	2.5
Dry Air Flow (CFM)	220
dBA Level (Front)	53
Est. Cooling Area (SQ. FT.)	300
Refrigerant	R410A

FEATURES

Display Panel	LED
Thermostat Control	Yes
Remote Controller	LCD Remote Controller
Control Button Type	Standard
Auto Swing	Yes
Auto Restart	Yes
Auto Door Open/Close System	Yes
Timer	24 Hr, On/Off
Fan Speed Cooling	2
Fan Only Speed	2
Compressor	Rotary
Indoor/Outdoor Fan Type	Blower
Type Air Discharge	Inclined and Top
Water Full Indicator	Yes
Outdoor Exhaust	Yes

MATERIALS/FINISHES

Available Colors	White
Easy-Roll Casters	Yes
Air Filter	Washable
Window Installation Kit	Yes

ELECTRICAL RATINGS

Voltage/60Hz	115
Watts	1,270
Rated Amps	11.3

DIMENSIONS

Product (WxHxD)	16.93" x 27.36" x 12.80"
Shipping (WxHxD)	19.29" x 34.65" x 15.55"
Net Weight	59.5 lbs.
Shipping Weight	70.5 lbs.

LIMITED WARRANTY

	1 Year Parts and Labor
--	------------------------

UPC CODES

LP1017WSR	772454068461
-----------	--------------

