

List updated August 4, 2015
For the most up-to-date list, visit
www.lutron.com/dimcflled

Dimmable CFL & LED bulbs

Compatible with Lutron 100W & 150W C-L® dimmers



Dimmable CFL & LED bulbs

Compatible with C·L[®] dimmers

List updated August 4, 2015
For the most up-to-date list, visit
www.lutron.com/dimcflled

This list is designed to help you select bulbs that are compatible with Lutron C·L dimmers. The CFL and LED bulbs on this list were extensively tested by Lutron; the Lutron C·L dimmers were evaluated by UL and meet applicable safety standards.

How to use this list

If you already have a bulb:

Use the “Find” tool in your browser or PDF viewer to search for the model number that’s printed on the bulb. Then choose a C·L dimmer that’s compatible with that bulb.

If you already have a C·L dimmer:

Use the table of contents to find the corresponding pages for that control, and then select a bulb from that list.

What does “compatible” mean?

Compatible means that the bulbs can be dimmed, although the bulb’s dimming performance may not match what you’re used to seeing when dimming an incandescent or halogen bulb. These bulbs have also been electrically tested to confirm that the control may be used up to its full rated CFL/LED load without affecting the life of the control.

Products on this list are considered compatible with the respective Lutron C·L dimmers. Depending on the quality of the bulb you select, compatible bulbs may still:

- have less dimming range than an incandescent or halogen bulb
- dim less smoothly than an incandescent or halogen bulb
- flicker or shimmer at certain light levels
- buzz

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers

List updated August 4, 2015
For the most up-to-date list, visit
www.lutron.com/dimcflled

For more information

If you'd like more information regarding bulb performance and test results, including dimming range, other dimmer options, and performance, please visit www.lutron.com/ledtool.

Warranty on your Lutron 100W C•L dimmer or 150W C•L dimmer will be void if used with bulbs that are not on this Lutron compatible bulb list.

Please note: Bulb variations in lamp design and construction affect performance. Bulb manufacturers can modify their bulbs at any time, without notice to Lutron. This prevents Lutron from ensuring ongoing compatibility. For up-to-date specifications, performance, and/or any related recall information about the bulb, please visit the bulb manufacturer's website.

This document provides information from manufacturers who are not Lutron agents or affiliates. The listing of a manufacturer or the existence of any external link to another website does not suggest that Lutron is endorsing the linked company, its products and/or its services. Purchasers should ask appropriate questions and request references before buying any products and/or entering a contract with any party. The information contained in this document is intended for illustrative and comparative purposes only, and is subject to change at any time. Lutron does not warrant that (a) the list of manufacturers is all-inclusive; (b) the information is complete, up-to-date, accurate and/or error-free; (c) the products and Lutron controls listed will always be compatible; and (d) that the information provided will be a viable or appropriate solution for your project needs. You are entirely responsible for and assume all risk for the use of the information.



LED bulbs for Caséta® Wireless in-wall dimmer

Caséta Wireless in-wall dimmer: PD-6WCL

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description
Cree	6W	BA19-04527OMF-12DE26-3U100	A19 4Flow, 2700K, 460 Lumen, E26
	6W	BA19-04550OMF-12DE26-3U100	A19 4Flow, 5000K, 460 Lumen, E26
	9.5W	BA19-08027OMF-12DE26-2U100	A19, Soft White, 2700K, 800 Lumen, Medium base
	9.5W	BA19-08027OMF-12DE26-2U500	A19, 2700K, 800 Lumen, E26, 60WE, 4pk
	9.5W	CR4-575L	4" Downlight, 2700K, 575 Lumen, Medium Base
	9.5W	CR6-575L	6" Downlight, 2700K, Medium Base
	9.5W	CR6-575L-GU24	6" Downlight, 2700K, GU24 Base
	9.5W	H1CR6TW62527E04	6" Downlight, 2700K, 625 Lumen
	12.5W	DRDL6-06227009-12DE26-1C100	6" Downlight, 2700K TW, 625 Lumen, E26 retrofit
	12.5W	DRDL6-06250009-12DE26-1C100	6" Downlight, 5000K TW, 625 Lumen, E26 retrofit
	18W	BA21-16027OMF-12DE26-1U100	A21, 2700K, 1600 Lumen, E26, 18W
	18W	BA21-16050OMF-12DE26-1U100	A21, 5000K, 1600 Lumen, E26, 18W
	18W	BPAR38-1503027T-12DE26-1U100	PAR38, 3000K, 1500 Lumen, 27 deg spot
	18W	BPAR38-1503047T-12DE26-1U100	PAR38, 3000K, 1500 Lumen, 47 deg flood
	EcoSmart	7W	ECS BR20 50WE CW 120 G1 BL
8W		ECS 19 CW 120	A19, Cool White, 5000K
8W		ECS 19 WW 120	A19, Warm White, 3000K
8W		ECS 20 CW FL 50WE 120	PAR20, 5000K, 490 Lumen
8W		ECS 20 WW FL 50WE 120	PAR20, 3000K, 450 Lumen
9.5W		ECO4-575L	4" Downlight, 2700K, 575 Lumen, Medium Base
9.5W		ECO4-575L-50K	4" Downlight, 5000K, 575 Lumen, Medium Base
9.5W		ECO4-575L-50K-GU24	4" Downlight, 5000K, GU24 Base
9.5W		ECO-575L	6" Downlight, 2700K, Medium Base
9.5W		ECO-575L-50K	6" Downlight, 5000K, Medium Base
9.5W		ECO-575L-50K-GU24	6" Downlight, 5000K, GU24 Base
9.5W		ECO-575L-GU24	6" Downlight, 2700K, GU24 Base
9.5W		ECS DN4 CW E26 120	4" Downlight, Daylight, 5000K, 650 Lumen, E26, retrofit
9.5W		ECS DN4 CW GU24 120	4" Downlight, Daylight, 5000K, 650 Lumen, GU24 base, retrofit
9.5W		ECS DN4 W27 E26 120	4" Downlight, Soft White, 2700K, 650 Lumen, E26 retrofit
9.5W		ECS DN4 W27 GU24 120	4" Downlight, Soft White, 2700K, 650 Lumen, GU24 base, retrofit
9.5W		ECS DN6 CW GU24 120	6" Downlight, Daylight, 5000K, 650 Lumen, GU24 base, retrofit
9.5W		ECS DN6 W27 GU24 120	6" Downlight, Soft White, 2700K, 650 Lumen, GU24 base, retrofit
10W		ECS BR30 65WE CW 120 DG	BR30, Daylight, 5000K, 700 Lumen, E26
10W		ECS BR30 65WE CW 120 DG 3PK	BR30, Daylight, 5000K, 700 Lumen, E26, 3pk
10W		ECS BR30 65WE W27 120 DG	BR30, Soft White, 2700K, 650 Lumen, E26
10W		ECS BR30 65WE W27 120 DG 3BX	BR30, Soft White, 2700K, 650 Lumen, E26, 3pk
10W		ECS BR30 65WE WW 120 DG	BR30, Warm White, 3000K, 650 Lumen, E26
10.5W		ECS 30 75WE WW GB FL 120	PAR30 Gimbal, 3000K, 750 Lumen, E26, 75WE
10.5W		ECS 30 75WE xxx GB xx 120	PAR30 Gimbal, Various color temperatures, 75WE
11.5W		ECS BR30 65WE CW 120	BR30, 5000K, Medium Base
11.5W		ECS BR30 65WE W27 120	BR30, 2700K, 650 Lumen, Medium Base
14W		ECS BR40 90WE CW 120 DG	BR40, Daylight, 5000K, 1050 Lumen, E26
14W		ECS BR40 90WE W27 120 DG	BR40, 2700K, 1000 Lumen, E26
15W		ECS BR30 W27 FL 120	BR30, Soft White, 2700K
24W	ECS 38 V2 WW FL 120	PAR38, Warm White, 3000K	
Energetic	17.5W	ELY17D-2BRW-VB†	BR40, 2700K, 1100 Lumen
Feit	4.5W	R14DM/LED	R14, Soft White, 2700K, 300 Lumen, E26, 40WE
	5W	MR16/GU10/DM/LED†	MR16, GU10 Base
	6.5W	BPMR16/GU10/DM/LED†	MR16, GU10 base
	6.5W	MR16/GU10/DM/LED†	MR16, GU10 base
	6.5W	R16DM/LED†	R16, Soft White, 2700K, 400 Lumen, E26, 40WE
	7.5W	PAR20DM/5K/LED†	PAR20, 5000K
	7.5W	PAR20DM/LED†	PAR20, 3000K
	8W	BPCER20/DM/LED	R20, 2700K, 450 Lumen, E26 Medium base (70 mA smooth reflector version)
	8W	R20/927/LED	R20, 2700K

† Requires a minimum of 2 lamps

†† Requires a minimum of 3 lamps

© Lutron Electronics Co., Inc. | PN 368-3266J

Dimmable CFL & LED bulbs

Compatible with C•L[®] dimmers

List Updated August 4, 2015



LED bulbs for Caséta[®] Wireless in-wall dimmer

Caséta Wireless in-wall dimmer: PD-6WCL

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description
Feit	8W	R20/930/LED	R20, 3000K
	8W	R20/950/LED	R20, 5000K,
	8W	R20DM/LEDG2/CAN	R20, 2700K
	13W	BPCEBR30LED	BR30
	13.5W	A19/OM800/5K/LED	A19, 5000K, Omni Directional
	13.5W	A19/OM800/LED	A19, 3000K, Omni Directional
	13.5W	BPCEA19/OM800/LED	A19, Omni Directional
	13.5W	BPCEA19/OM800/LED/CAN	A19, Omni Directional
	14W	LEDR56/830	Downlight, 3000K, 925 Lumen, retrofit kit
	17W	BR40/DM/LED [†]	BR40, 2700K, 1065 Lumen
20.5W	LEDR56/827	5" or 6" Downlight, 2700K, 1245 Lumen	
GE	8W	LED8DA19/827	A19, 2700K, 450 Lumen, E26
	14W	LED14DA21V2/827W	A21, 2700K, 1100 Lumen, E26
Lighting Science	8W	DFN 19 CW 120	A19, Cool White, 5000K
	8W	DFN 19 NW 120	A19, Neutral White, 4000K
	8W	DFN 19 W27 120	A19, Warm White, 2700K
	8W	DFN 19 WW 120	A19, Warm White, 3000K
	10.5W	LS 30 75WE xxx GB xx 120	PAR30, various color temperatures
	11.5W	DFN BR30 65WE CW 120	BR30, Cool White, 5000K, Medium base
	11.5W	DFN BR30 65WE NW 120	BR30, Neutral White, 4000K, Medium base
	11.5W	DFN BR30 65WE W27 120	BR30, Warm White, 2700K, Medium base
	11.5W	DFN BR30 65WE WW 120	BR30, Warm White, 3000K, Medium base
	13W	LS GLP6 W27 120 WH S1 BX	6" Downlight, 2700K, E26 retrofit
	15W	DFN BR30 CW FL 120	BR30, Cool White, 5000K
	15W	DFN BR30 NW FL 120	BR30, Neutral White, 4000K
	15W	DFN BR30 W27 FL 120	BR30, Warm White, 2700K
	15W	DFN BR30 WW FL 120	BR30, Warm White, 3000K
	24W	DFN 38 CW V2 FL 120	PAR38, Cool White, 5000K
	24W	DFN 38 CW V2 NFL 120	PAR38, Cool White, 5000K
	24W	DFN 38 NW V2 FL 120	PAR38, Neutral White, 4000K
	24W	DFN 38 NW V2 NFL 120	PAR38, Neutral White, 4000K
	24W	DFN 38 W27 V2 FL 120	PAR38, Warm White, 2700K
	24W	DFN 38 W27 V2 NFL 120	PAR38, Warm White, 2700K
	24W	DFN 38 WW V2 FL 120	PAR38, Warm White, 3000K
	24W	DFN 38 WW V2 NFL 120	PAR38, Warm White, 3000K
Lumapro	8W	8A19/LED/DIM/30	A19, Warm White, 3000K (6GEM2)
	8W	8A19/LED/DIM/50	A19, Cool White, 5000K (6GEM3)
Philips	4.5W	9290002439	Candle, Warm White, 2700K, 320 Lumen, E26 base, Post Light
	4.5W	9290002797 ^{††}	Candle, 2700K, 330 Lumen, E26, blunt tip
	4.5W	9290002889 ^{††}	Candle, 2700K, 330 Lumen, E12, blunt tip
	4.5W	9290002890 ^{††}	A15, 2700K, 330 Lumen, E12
	4.5W	9290002891 ^{††}	A15, 2700K, 330 Lumen, E26
	6W	9290002242	MR16, 3000K, 300 Lumen, GU10 base
	6.5W	9290011347 (455741)	A19, Warm Glow, 450 Lumen
	7W	9290002706	A19 SlimStyle, Daylight, 5000K, 450 Lumen, E26
	8W	9290002267	A19, 2700K, 470 Lumen
	8W	9290002295	A19, 5000K, 470 Lumen
	8W	9290002329	PAR20, 3000K, 470 Lumen, E26
	8.5W	9290002543	BR30, 5000K, 730 Lumen, 8.5W
	9.5W	9290011117	BR30, 2700K, 730 Lumen, WarmGlow to 2200K (Nov 2014 or later)
	9.5W	9290011118 (452359)	BR30 SlimStyle, 2700K, 650 Lumen, E26, 65WE
	9.5W	9290011118 (452383)	BR30 SlimStyle, 2700K, 650 Lumen, E26, 65WE
	9.5W	9290011118 (452417)	BR30 SlimStyle, 2700K, 650 Lumen, E26, 65WE
	9.5W	9290011119 (452441)	BR30 SlimStyle, 5000K, 650 Lumen, E26, 65WE
9.5W	9290011119 (452466)	BR30 SlimStyle, 5000K, 650 Lumen, E26, 65WE	
9.5W	9290011119 (452482)	BR30 SlimStyle, 5000K, 650 Lumen, E26, 65WE	
10.5W	9290002544	BR30, 2700K, 730 Lumen	

[†] Requires a minimum of 2 lamps

^{††} Requires a minimum of 3 lamps

© Lutron Electronics Co., Inc. | PN 368-3266J

Dimmable CFL & LED bulbs

Compatible with C•L[®] dimmers

List Updated August 4, 2015



LED bulbs for Caséta[®] Wireless in-wall dimmer

Caséta Wireless in-wall dimmer: PD-6WCL

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description
Philips	10.5W	9290002707	A19 SlimStyle, Soft White, 2700K, 800 Lumen, 3pk
	11W	9290002268	A19, 2700K, 830 Lumen
	11W	9290002296	A19, 5000K, 830 Lumen
	11W	9290011113	PAR30L, 3000K, ? Lumen, E26
	12W	9290002580 (431392)	BR40, 2700K, 800 Lumen
	13W	9290002201	PAR30, 3000K, 750 Lumen
	13W	9290002233	PAR30, 2700K, 784 Lumen
	13W	9290002234	PAR30, 2700K, 770 Lumen
	13W	9290002323	PAR30, 5000K, 850 Lumen
	13W	9290011120	A21 SlimStyle, 2700K, 1100 Lumen
	13W	9290002523 13PAR38/F25 3000 DIM AF RO	PAR38, 3000K, 950 Lumen
	14.5W	9290002199	BR40, 2700K, 832 Lumen
	15W	9290002595	A21, Soft White, 2700K, 1180 Lumen, E26
	15W	9290011111	PAR38, 3000K, 1050 Lumen, E26, Flood
	15W	9290011112	PAR38, 5000K, 1050 Lumen, E26, Flood
	17W	9290002018 [†]	A21, 2700K
	17W	17E26A21D [†]	A21, 2700K
	18W	9290002202	PAR38, 3000K, 951 Lumen, Medium Base
	18W	9290002236	PAR38
	18W	9290002237	PAR38
	18W	9290002245	PAR38, 2700K, 938 Lumen
	18W	9290002246	PAR38
	18W	9290002307	PAR38
	18W	9290002308	PAR38
	18W	9290002309	PAR38
	18W	9290002310	PAR38
	18W	9290002311	PAR38
	18W	18E26PAR38-3	PAR38
18W	18E26PAR38-4	PAR38	
Samsung	7W	STIPLW8300711AB	SI-P8V071AB0US
Satco	11W	S9084	PAR30, 3000K, 780 Lumen, E26, short neck, 25° Beam
	11W	S9085	PAR30, 4000K, 780 Lumen, E26, short neck, 25° Beam
	11W	S9086	PAR30, 3000K, 780 Lumen, E26, short neck, 40° Beam
	11W	S9087	PAR30, 4000K, 780 Lumen, E26, short neck, 40° Beam
	11W	S9088	PAR30, 3000K, 780 Lumen, E26, long neck, 25° Beam
	11W	S9089	PAR30, 4000K, 780 Lumen, E26, long neck, 25° Beam
	11W	S9090	PAR30, 3000K, 780 Lumen, E26, long neck, 40° Beam
	11W	S9091	PAR30, 4000K, 780 Lumen, E26, long neck, 40° Beam
	17W	S9092	PAR38, 3000K, 1200 Lumen, E26, 25° beam
	17W	S9093	PAR38, 4000K, 1200 Lumen, E26, 25° beam
	17W	S9094	PAR38, 3000K, 1200 Lumen, E26, 40° beam
	17W	S9095	PAR38, 4000K, 1200 Lumen, E26, 40° beam
Solais	7W	LRP20/25/27K	PAR20, 2700K, 475 Lumen, E26, 25° Beam
	7W	LRP20/25/30K	PAR20, 3000K, 500 Lumen, E26, 25° Beam
	7W	LRP20/40/27K	PAR20, 2700K, 475 Lumen, E26, 40° Beam
	7W	LRP20/40/30K	PAR20, 3000K, 500 Lumen, E26, 40° Beam
	11W	LR20/25/27K/675/xx	PAR20, 2700K, 675 Lumen, E26, narrow flood
	11W	LR20/25/30K/750	PAR20, 3000K, 750 Lumen, E26, narrow flood
	11W	LR20/40/27K/675/xx	PAR20, 2700K, 675 Lumen, E26, wide flood
	11W	LR20/40/30K/750/xx	PAR20, 3000K, 750 Lumen, E26, wide flood
	16W	LR30/10/27K/1100/xx	PAR30, 2700K, 1100 Lumen, E26, short neck, 10° Beam
	16W	LR30/10/30K/1125/xx	PAR30, 3000K, 1125 Lumen, E26, short neck, 10° Beam
	16W	LR30/10/30K/1200/xx	PAR30, 3000K, 1200 Lumen, E26, short neck, 10° Beam
	16W	LR30/15/27K/1100/xx	PAR30, 2700K, 1100 Lumen, E26, short neck, 15° Beam
	16W	LR30/15/30K/1125/xx	PAR30, 3000K, 1125 Lumen, E26, short neck, 15° Beam
	16W	LR30/15/30K/1200/xx	PAR30, 3000K, 1200 Lumen, E26, short neck, 15° Beam

[†] Requires a minimum of 2 lamps

^{††} Requires a minimum of 3 lamps

© Lutron Electronics Co., Inc. | PN 368-3266J



LED bulbs for Caséta[®] Wireless in-wall dimmer

Caséta Wireless in-wall dimmer: PD-6WCL

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description
Solais	16W	LR30/25/27K/1100/xx	PAR30, 2700K, 1100 Lumen, E26, short neck, 25° Beam
	16W	LR30/25/30K/1125/xx	PAR30, 3000K, 1125 Lumen, E26, short neck, 25° Beam
	16W	LR30/25/30K/1200/WH	PAR30, 3000K, 1200 Lumen, E26, short neck, 25° Beam
	16W	LR30/40/27K/1100/xx	PAR30, 2700K, 1100 Lumen, E26, short neck, 40° Beam
	16W	LR30/40/30K/1125/xx	PAR30, 3000K, 1125 Lumen, E26, short neck, 40° Beam
	16W	LR30/40/30K/1200/xx	PAR30, 3000K, 1200 Lumen, E26, short neck, 40° Beam
	16W	LRP38/25/27K	PAR38, 2700K, 1025 Lumen, E26, 25° Beam
	16W	LRP38/25/30K	PAR38, 3000K, 1100 Lumen, E26, 25° Beam
	16W	LRP38/40/27K	PAR38, 2700K, 1025 Lumen, E26, 40° Beam
	16W	LRP38/40/30K	PAR38, 3000K, 1100 Lumen, E26, 40° Beam
	20W	LR38/25/30K/1450/SL	PAR38, 3000K, 1450 Lumen, E26, 15° Beam
	28W	LR38/15/27K/2000/xx	PAR38, 2700K, 2000 Lumen, E26
	28W	LR38/15/30K/2100/xx	PAR38, 3000K, 2100 Lumen, E26
	28W	LR38/25/27K/2000/xx	PAR38, 2700K, 2000 Lumen, E26
	28W	LR38/25/30K/2100/xx	PAR38, 3000K, 2100 Lumen, E26
	28W	LR38/40/27K/2000/xx	PAR38, 2700K, 2000 Lumen, E26
	28W	LR38/40/30K/2100/xx	PAR38, 3000K, 2100 Lumen, E26
	Sylvania	6W	79643
7W		LED7A19/DIM/0/SE/830 (78214)	A19, 3000K to 2000K, 450 Lumen, E26, Sunset Effect
7W		LED7A19/DIM/0/SE/830/RP (78213)	A19, 3000K to 2000K, 450 Lumen, E26, Sunset Effect
8W		LED8A/DIM/F/827	A19, 2700K
8W		LED8A/DIM/F/830	A19, 3000K
8W		LED8A19DIM0827RP	A19, 2700K, 470 Lumen, E26
8W		LED8PAR16/DIM/930/FL36/P/LW	PAR16, Soft White, 390 Lumen
8W		LED8PAR16/GU10/DIM/930/FL36/RP	PAR16, GU10, Soft White, 390 Lumen
9W		LED/550/RT4/827/FL80/WRFL	4" Downlight, 2700K
9W		LED/550/RT4/830/FL80/WRFL	4" Downlight, 3000K
10W		LED10A19/DIM/0/SE/830	A19, 3000K, 800 Lumen
10W		LED10A19/DIM/0/SE/830/RP (78215)	A19, 3000K, 800 Lumen
10.5W		LED10A19/DIM/CL/O/827 (79146)	A19, 2700K, 800 Lumen, E26, 60WE
10.5W		LED10A19/DIM/CL/O/827/BL (79147)	A19, 2700K, 800 Lumen, E26, 60WE
10.5W		LED10A19/DIM/CL/O/827/G4 (79142)	A19, 2700K, 800 Lumen, E26, 60WE
10.5W		LED10A19/DIM/CL/O/827/G4/BL (79143)	A19, 2700K, 800 Lumen, E26, 60WE
10.5W		LED10A19/DIM/CL/O/827/RP (79644)	A19, 2700K, 800 Lumen, E26, 60WE
10.5W		LED10A19/DIM/CL/O/850/G4 (79144)	A19, 5000K, 800 Lumen, E26, 60WE
10.5W		LED10A19/DIM/CL/O/850/G4/BL (79145)	A19, 5000K, 800 Lumen, E26, 60WE
11W		LED11BR30/DIM/HO/827/G3 (78413)	BR30, 2700K, 800 Lumen, E26
11W	LED11BR30/DIM/HO/827/G3/RP (78415)	BR30, 2700K, 800 Lumen, E26	
11W	LED11BR30/DIM/HO/827/G3/RP (79121)	BR30, 2700K, 800 Lumen, E26	
11W	LED11PAR20/DIM/930/FL30/P2	PAR20, Soft White, 550 Lumen	
12W	LED12BR30/DIM/HO/827	BR30, 2700K, Medium base	
12W	LED12BR30/DIM/HO/827/HVP	BR30, 2700K, Medium base	
17W	LED17PAR30LN/DIM/830/WSP15/P	PAR30, 3000K, 1200 Lumen, E26, spot	
17W	LED17PAR30LN/DIM/830/WSP20	PAR30, 3000K, 1200 Lumen, E26, wide spot	

† Requires a minimum of 2 lamps
 †† Requires a minimum of 3 lamps
 © Lutron Electronics Co., Inc. | PN 368-3266J

Dimmable CFL & LED bulbs

Compatible with C•L[®] dimmers

List Updated August 4, 2015



LED bulbs for Caséta[®] Wireless in-wall dimmer

Caséta Wireless in-wall dimmer: PD-6WCL

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description
Sylvania	17W	LED17PAR30LN/DIM/P/930/NFL25 [†]	PAR30, 3000K, 900 Lumen
	20W	LED20PAR38/DIM/930/FL40/P2	PAR38, 3000K, 1000 Lumen,
	21W	LED21/PAR38/DIM/P/930/FL30/HVP	PAR38, Warm White, 3000K, 1100 Lumen, E26, 21W
	21W	LED21PAR38/DIM/P/930/FL30	PAR38, 3000K, 1100 Lumen
Utilitech	3W	LG161/2DM/IF/LED [†]	G16.5, Warm White, 3000K, 200 Lumen, E12 base, frosted
	4.5W	LR14DMLED	R14, Soft White, 2700K, 300 Lumen, E26, 40WE
	4.8W	LA15DM/CL/300/LED [†]	A15, Warm White, 3000K, 300 Lumen, E26, clear
	4.8W	LA15DM/IF/300/LED [†]	A15, Warm White, 3000K, 300 Lumen, E26, frosted
	4.8W	LA15DMC/CL/300/LED [†]	A15, Warm White, 3000K, 300 Lumen, E12 base, clear
	4.8W	LCFCDM/300/LED [†]	Candle, Warm White, 3000K, 300 Lumen, E12 base, clear flame tip
	4.8W	LCFFDM/300/LED [†]	Candle, Warm White, 3000K, 300 Lumen, E12 base, frosted flame tip
	4.8W	LEFCDM/300/LED [†]	Candle, Warm White, 3000K, 300 Lumen, E26 base, clear flame tip
	4.8W	LG161/2DM/CL/300/LED [†]	G16.5, Warm White, 3000K, 300 Lumen, E12 base, clear
	4.8W	LG161/2DM/IF/300/LED [†]	G16.5, Warm White, 3000K, 300 Lumen, E12 base, frosted
	4.8W	LGMDM/CL/300/LED [†]	G16.5, Warm White, 3000K, 300 Lumen, E26, clear
	5W	LMR16GU10DM/LED [†]	MR16, GU10 Base
	6.5W	LMR16/GU10/DM/LED [†]	MR16, GU10 base
	6.5W	LMR16DMGU10 [†]	MR16, GU10 base
	6.5W	LR16DMLED [†]	R16, Soft White, 2700K, 400 Lumen, E26, 40WE
	7.5W	LPAR20DM/5K/LED [†]	PAR20, 5000K
	7.5W	LPAR20DM/LED [†]	PAR20, 3000K
	8W	LG25DM/LEDG2 [†]	G25, Warm White, 3000K, 510 Lumen, E26
	8W	LR20DMLEDG2	R20, 2700K, 450 Lumen, E26 Medium base (70 mA smooth reflector version)
	9W	LR20HO/LED/G2	R20, Soft White, 650 Lumen, E26, flood
	9W	R20HO/LED/G2	R20, Soft White, 650 Lumen, E26, flood
	11W	DLS02-04A27D1E-WH-F1	4" Downlight, 2700K, 600 Lumen, E26 retrofit
	11W	DLS02-04A27D1E-WH-F2	4" Downlight, 2700K, 600 Lumen, E26 retrofit 2pk
	11W	DLS02-06A27D1E-WH-F2	5" or 6" Downlight, 2700K, 700 Lumen, E26 retrofit 2pk
	11W	DLS02-41127D1E-WF1	4" Downlight, Soft White, 2700K, 650 Lumen, E26 retrofit
	12W	LPAR30L/LEDG7/2	PAR30L, 3000K, 800 Lumen, E26, long neck, 2PK
	12W	MQTL1017-LED11.5K850 [†]	Downlight, 5000K, 800 Lumen, E26 retrofit kit
	13W	DLS02-06A50D1E-WH-F1	5" or 6" Downlight, 5000K, 700 Lumen, E26 retrofit
	13W	DLS02-61327D1E-WF1	5" or 6" Downlight, Soft White, 2700K, 800 Lumen, E26 retrofit
	13W	DLS02-61350D1E-WF1	5" or 6" Downlight, Daylight, 5000K, 800 Lumen, E26 retrofit
	13W	LBR30DM/LEDG2	BR30
	13.5W	LA19/OM800/LED	A19, 3000K, 800 Lumen, Omni Directional
	15W	LBR30HO/LED/G2	BR30, Soft White, 1150 Lumen
16W	LPAR38LEDG72	PAR38, 3000K, 950 Lumen, 2PK	
17W	BPCEBR40/DM/LED [†]	BR40	
17W	LBR40DM/LED [†]	BR40, 2700K, 1065 Lumen	
17.5W	YGA08A35-17.5W-827 [†]	BR40, 2700K, 1100 Lumen	
20W	LBR40HO/LED/G2	BR40, Soft White, 1400 Lumen	
20.5W	LPAR381400LEDG72	PAR38, 1450 Lumen, 2PK	
Westinghouse	8W	8A19/LED/DIM/30	A19, Warm White, 3000K
	8W	8A19/LED/DIM/50	A19, Cool White, 5000K

[†] Requires a minimum of 2 lamps

^{††} Requires a minimum of 3 lamps

© Lutron Electronics Co., Inc. | PN 368-3266J

Dimmable CFL & LED bulbs

Compatible with C•L[®] dimmers

List Updated August 4, 2015



CFL bulbs for Caséta[®] Wireless in-wall dimmer

Caséta Wireless in-wall dimmer: PD-6WCL

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description
GE	26W	FLE26HT3/2/DV/SW	Spiral
	14W	4R2014TD	R20, TruDim, 2700K
	14W	4R2014TD30K	R20, TruDim, 3000K
TCP	14W	4R2014TD35K	R20, TruDim, 3500K
	14W	4R2014TD41K	R20, TruDim, 4100K
	14W	4R2014TD50K	R20, TruDim, 5000K
	14W	4R2014TD65K	R20, TruDim, 6500K

† Requires a minimum of 2 lamps

†† Requires a minimum of 3 lamps

© Lutron Electronics Co., Inc. | PN 368-3266J

Dimmable CFL & LED bulbs

Compatible with C•L[®] dimmers

List Updated August 4, 2015



LED bulbs for Caséta[®] Wireless plug-in lamp dimmer

Caséta Wireless plug-in lamp dimmer: PD-3PCL

Maximum wattage controlled: 100W



Brand	Wattage	Model	Description
Cree	6W	BA19-04527OMF-12DE26-1U100	A19, Warm Soft White, 2700K, 450 Lumen, Medium base
	6W	BA19-04527OMF-12DE26-2U100	A19, Warm Soft White, 2700K, 450 Lumen, Medium base
	6W	BA19-04550OMF-12DE26-2U500	A19, 5000K, 450 Lumen, 40WE, 4pk
	9.5W	BA19-08027OMF-12DE26-2U100	A19, Soft White, 2700K, 800 Lumen, Medium base
	9.5W	BA19-08027OMF-12DE26-2U500	A19, 2700K, 800 Lumen, E26, 60WE, 4pk
	18W	BA21-16027OMF-12DE26-1U100	A21, 2700K, 1600 Lumen, E26, 18W
EcoSmart	18W	BA21-16050OMF-12DE26-1U100	A21, 5000K, 1600 Lumen, E26, 18W
	8W	ECS 19 CW 120	A19, Cool White, 5000K
Feit	8W	ECS 19 WW 120	A19, Warm White, 3000K
	7.5W	PAR20DM/5K/LED [†]	PAR20, 5000K
	7.5W	PAR20DM/LED [†]	PAR20, 3000K
	9.5W	BPCER20/DM/LED	PAR20
	9.5W	PAR20/5K/LEDG5	PAR20, 5000K
	9.5W	PAR20/5K/LEDG5/CAN	PAR20, 5000K
	9.5W	PAR20/LEDG5	PAR20, 3000K, 450 Lumen
	9.5W	PAR20/LEDG5/CAN	PAR20
	10W	G25/DM/LED	G25, 3000K
	13.5W	A19/OM800/5K/LED	A19, 5000K, Omni Directional
	13.5W	A19/OM800/LED	A19, 3000K, Omni Directional
	13.5W	BPCEA19/OM800/LED	A19, Omni Directional
	13.5W	BPCEA19/OM800/LED/CAN	A19, Omni Directional
GE	18W	LED18D38W827/15	PAR38, 2700K, E26, 15° Beam
	18W	LED18D38W827/25	PAR38, 2700K, E26, 25° Beam
	18W	LED18D38W827/40	PAR38, 2700K, E26, 40° Beam
	18W	LED18D38W830/15	PAR38, 3000K, 1400 Lumen, E26, 15° Beam
	18W	LED18D38W830/25	PAR38, 3000K, 1400 Lumen, E26, 25° Beam
	18W	LED18D38W830/40	PAR38, 3000K, 1400 Lumen, E26, 40° Beam
	18W	LED18D38W927/15	PAR38, 2700K, 1100 Lumen, E26, 15° Beam
	18W	LED18D38W927/25	PAR38, 2700K, 1100 Lumen, E26, 25° Beam
	18W	LED18D38W927/40	PAR38, 2700K, 1100 Lumen, E26, 40° Beam
	18W	LED18D38W930/15	PAR38, 3000K, 1200 Lumen, E26, 15° Beam
	18W	LED18D38W930/25	PAR38, 3000K, 1200 Lumen, E26, 25° Beam
	18W	LED18D38W930/40	PAR38, 3000K, 1200 Lumen, E26, 40° Beam
	Lighting Science	8W	DFN 19 CW 120
8W		DFN 19 NW 120	A19, Neutral White, 4000K
8W		DFN 19 W27 120	A19, Warm White, 2700K
8W		DFN 19 WW 120	A19, Warm White, 3000K
Lumapro	8W	8A19/LED/DIM/30	A19, Warm White, 3000K (6GEM2)
	8W	8A19/LED/DIM/50	A19, Cool White, 5000K (6GEM3)
Philips	8W	9290002267	A19, 2700K, 470 Lumen
	8W	9290002295	A19, 5000K, 470 Lumen
	9.5W	9290011345 (455840)	A19, Soft White, 2200-2700K, 800 Lumen, E26
	11W	9290002268	A19, 2700K, 830 Lumen
	11W	9290002296	A19, 5000K, 830 Lumen
	13W	9290011120	A21 SlimStyle, 2700K, 1100 Lumen
	14.5W	9290002199	BR40, 2700K, 832 Lumen
	15W	9290002595	A21, Soft White, 2700K, 1180 Lumen, E26
Samsung	17W	9290002018	A21, 2700K
	17W	17E26A21D	A21, 2700K
Satco	7W	STIPLW8300711AB	SI-P8V071AB0US
	10.5W	S9037	A19, 2700K, 810 Lumen, E26
	10.5W	S9038	A19, 3500K, 830 Lumen, E26
Sylvania	10.5W	S9039	A19, 5000K, 870 Lumen, E26
	8W	LED8A/DIM/F/827	A19, 2700K
	8W	LED8A/DIM/F/830	A19, 3000K
	8W	LED8A19DIMO827RP	A19, 2700K, 470 Lumen, E26
	10.5W	LED10A19/DIM/CL/O/827 (79146)	A19, 2700K, 800 Lumen, E26, 60WE

† Requires a minimum of 2 lamps

†† Requires a minimum of 3 lamps

© Lutron Electronics Co., Inc. | PN 368-3266J

Dimmable CFL & LED bulbs

Compatible with C•L[®] dimmers

List Updated August 4, 2015



LED bulbs for Caséta[®] Wireless plug-in lamp dimmer

Caséta Wireless plug-in lamp dimmer: PD-3PCL

Maximum wattage controlled: 100W



Brand	Wattage	Model	Description
Sylvania	10.5W	LED10A19/DIM/CL/O/827/BL (79147)	A19, 2700K, 800 Lumen, E26, 60WE
	10.5W	LED10A19/DIM/CL/O/827/G4 (79142)	A19, 2700K, 800 Lumen, E26, 60WE
	10.5W	LED10A19/DIM/CL/O/827/G4/BL (79143)	A19, 2700K, 800 Lumen, E26, 60WE
	10.5W	LED10A19/DIM/CL/O/827/RP (79644)	A19, 2700K, 800 Lumen, E26, 60WE
	10.5W	LED10A19/DIM/CL/O/850/G4 (79144)	A19, 5000K, 800 Lumen, E26, 60WE
	10.5W	LED10A19/DIM/CL/O/850/G4/BL (79145)	A19, 5000K, 800 Lumen, E26, 60WE
Utilitech	7.5W	LA19DM/LEDG2	A19, 3000K, 450 Lumen
	7.5W	LPAR20DM/5K/LED [†]	PAR20, 5000K
	7.5W	LPAR20DM/LED [†]	PAR20, 3000K
	8W	LG25DM/LEDG2	G25, Warm White, 3000K, 510 Lumen, E26
	9.5W	LPAR20/5K/LEDG5	PAR20, 5000K, 500 Lumen
	9.5W	LPAR20/LEDG5	PAR20, 3000K, 450 Lumen
	9.5W	LPAR20DM/SP/LED	PAR20, 3000K, 465 Lumen, Spot
	10W	LG25/DM/LED	G25, 3000K
Westinghouse	13.5W	LA19/OM800/LED	A19, 3000K, 800 Lumen, Omni Directional
	8W	8A19/LED/DIM/30	A19, Warm White, 3000K
	8W	8A19/LED/DIM/50	A19, Cool White, 5000K

† Requires a minimum of 2 lamps

†† Requires a minimum of 3 lamps

© Lutron Electronics Co., Inc. | PN 368-3266J

Dimmable CFL & LED bulbs

Compatible with C•L[®] dimmers

List Updated August 4, 2015



CFL bulbs for Caséta[®] Wireless plug-in lamp dimmer

Caséta Wireless plug-in Lamp dimmer: PD-3PCL

Maximum wattage controlled: 100W



Brand	Wattage	Model	Description
GE	26W	FLE26HT3/2/DV/SW	Spiral

† Requires a minimum of 2 lamps
†† Requires a minimum of 3 lamps
© Lutron Electronics Co., Inc. | PN 368-3266J